

Blinker Light (Traffic sign)												
Major Product Category - Signage & Accessories (5512)										Version- 1		
Sub category - Signage (551217)												
Item - Traffic Signs (Blinker Light) UNSPC: 55121710, ITC-HS code-94054090.												
S.No	Parameters		Value 1	Value2	Value 3	Value	Validation Rule	Whether Filter required	Priority	Unit	Demand aggregation	
1	Construction	Ch	Single piece metal (min 3 mm thick)cabinet with thick Black powder coating WITH polycarbonate front glass. Provided with hooks for hanging									
2	Length	N					must declare			cms		
3	Height	N					must declare			cms		
4	Width	N					must declare			cms		
5	Display (colour plate)	Ch	As per user requirement									
6	Front glass shall be heat and shock resistance and should not break if water droplets fall on it while the blinker in use.	Ch	Yes									
7	Auto Flashing feature with variable ON/OFF	Ch	Yes									
8	Adjustment for reducing intensity of LED	Ch	Yes									
9	Light Sensor to OFF the blinker in day and ON in dark	Ch	Yes									
10	Single button to activate & deactivate the blinker	Ch	Yes									
11	Ingress protection	Ch	IP 65 or better									
12	Operating environment	Ch	upto 95% R.H at 40 degree C									
13	Built in battery /capacity (Maintenance free battery.)	Ch	SMF lead acid/ 12V/7Ah		SMF lead acid/12V/9Ah							

14	Battery charging time.(Max.)	N	8 Hrs								
15	Battery Back-up time with cvntinuous	N					>24			hrs	
16	Input Power	Ch	230V +/- 10 %, 50 Hz AC								
17	Warranty	N	3	5				Yes	1	years	
18	Availability of Test Reports from Central Govt/NABL/ILAC accredited Lab covering all the parameters as per specifications	Ch									must declare
19	Test Report No.	Ch									must declare
20	Test Report Date	Ch									must declare
21	Name of Test Lab	Ch									must declare
22	Address of the Test Lab	Ch									must declare

S K JAIN
DQA, HYD

ROHIT
KUMAR
DDQA, HYD